


Draka UC500 Cat. 6a F/FTP 23 AWG LSZH

Ethernet cable up to 500 MHz



Application

Generic cabling systems
Primary (Campus), Secondary (Riser), Tertiary (Horizontal)
IEEE 802.3 10Base-T; 100Base-T; 1000Base-T; 10GBase-T
IEEE 802.5 16 MB; ISDN; TPDDI; ATM
IEEE 802.3af (PoE); IEEE 802.3at (PoE+)

Standards

ANSI EIA/TIA 568-2.D: 2018;
ISO/IEC 11801-1: 2017 / ISO/IEC 11801-2: 2017;
IEC 61156-5: 2012;
EN 50173-1: 2011 / EN 50173-2: 2007 including amendment A1: 2010;
EN 50288-10-1: 2012

Construction

Conductor	Solid copper wire Nom. $\geq \varnothing 0.546$ mm (23AWG)
Insulation	Foam PE, Nom. $\varnothing 1.25$ mm
Twisting	2 cores to the pair
Cable Lay Up	4 x pairs to the core
Pair Screen	High Performance Individual Pair Screen
Overall Screen	Aluminum Laminated Foil with Tinned copper drain wire (0.4 mm)
Sheath / Color	LSZH (BLUE RAL5024 or GREEN RAL6018)
Outer Diameter	Nom. $\varnothing 7.5$ mm
Approximate Weight	Nom. 52.0 kg/km

Mechanical properties

Bend radius	With Load	$\geq 8 \times \text{O.D (60.0mm)}$
	No Load	$\geq 4 \times \text{O.D (30.0mm)}$
Temperature range	During operation	-20°C to +60°C
	During installation	0°C to +50°C
Maximum Pulling Force	During installation	100 N

Electrical properties

Mean Characteristic Impedance	1-100 MHz	$100 \pm 15 \Omega$
	100-250 MHz	$100 \pm 22 \Omega$
	250-500 MHz	$100 \pm 25 \Omega$
DC Loop Resistance		$\leq 187.6 \Omega/\text{km}$
DC Resistance Unbalance		$\leq 4\%$
Mutual Capacitance (@1 kHz)		$\leq 5.6 \text{ nF}/100\text{m}$
Capacitance unbalance	Pair to ground	$\leq 330 \text{ pF}/100\text{m}$
Velocity of Propagation		Nom. 75%
Propagation Delay (@500 MHz)		$\leq 536.0 \text{ ns}/100\text{m}$
Delay Skew		$\leq 45 \text{ ns}/100\text{m}$

Freq. (MHz)	Max. Attenuation (dB)	Min. NEXT (dB)	Min. PS-NEXT (dB)	Min. ACR-F (dB)	Min. PS-ACRF (dB)	Min. Return Loss (dB)
1.0	2.1	74.3	72.3	67.8	64.8	20.0
4.0	3.8	65.3	63.3	55.8	52.8	23.0
16.0	7.5	56.2	54.2	43.7	40.7	25.0
31.25	10.5	51.9	49.9	37.9	34.9	23.6
62.5	15.0	47.4	45.4	31.9	28.9	21.5
100.0	19.1	44.3	42.3	27.8	24.8	20.1
250.0	31.1	38.3	36.3	19.8	16.8	17.3
300.0	34.3	37.1	35.1	18.3	15.3	16.8
400.0	40.1	35.3	33.3	15.8	12.8	15.9
500.0	45.3	33.8	31.8	13.8	10.8	15.2

Note1: All tests include 401 points swept frequency measurements

Note2: All electrical characteristics are given at 20°C

Note3: All above stated values are nominal and subject to changes

Note4: Transmission performance based on 100 m (328 ft)

Fire Rating

LSZH IEC 60332-1-1: 2015; IEC 60332-1-2: 2015;
IEC 60754-1: 2011; IEC 60754-2: 2011;
IEC 61034-2: 2013

Ordering Information

SAP 1C	UC P/N	Product Description	P.U
60067216	84075	UC 500 Cat 6a F/FTP 23 AWG LSZH, Blue, IEC 60332-1	500m/reel
60067569	84075GN	UC 500 Cat 6a F/FTP 23 AWG LSZH, Green, IEC 60332-1	500m/reel

Marking:

Marked in 1 meter intervals as follows:

DRAKA UC500 F/FTP LSZH CAT 6a CABLE P/N <PART NUMBER> VERIFIED TO EN 50288 ISO/IEC 11801 ANSI/TIA-568-C.2 <FC> <BATCHCODE> <XXX>M

<PART NUMBER>: Draka product part number

<FC>: Draka defined factory Code

<BATCHCODE>: Factory defined tracking code MM/YYYY or WW/YYYY

<XXX>: Increasing length marking by 1 metre (Meter marking is 1-500m with larger number in the outside layer of the drum)

Logistic

Packing:

Wooden drum.

Delivery Lengths:

500m per drum.

Enquiries

Please contact our local sales office or mms.asia@prysmiangroup.com

Multimedia Solutions is the data communication portfolio of Prysmian Group and comprises all the necessary portfolio of cable solutions for data communication.

Ask about UC CONNECT for a complete Structure Cabling Solutions with 25 Years System Warranty.

Visit www.DrakaUC.com for more information.

© PRYSMIAN GROUP 2019, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.