




DRAKA RS485 2P 22AWG FPE

Serial Data Communication Cable



Application

For multi-dropped, medium-speed, serial data communication in electrically noisy industrial environments. Application includes industrial networks using RS-485 / RS-422 / RS-232 transceivers, RS-422 systems for Process Automation (chemicals, brewing, paper mills), factory automation (autos, metal fabrication), HVAC, security, motor control and motion control.

Standards

EIA/TIA RS-485

Construction

Conductor	Stranded Tinned Copper, 22AWG, Diameter 7 x 0.254mm	Ø0.76mm
Insulation	Foam-PE	$arnothing$ 2.2 \pm 0.2 mm
Color code	Pair 1: White*Orange, Pair 2: White*Blue	
1 st screen	1 x AL-Mylar Wrap, Overlapping	>= 25 %
Drain wire	7/0.254mm Stranded Tinned Copper	
Braid shield	Tinned copper	
Coverage	≥85%	
Jacket	LSZH(Black) / PVC(Grey)	Ø9.0 ± 0.2mm





DRAKA RS485 2P 22AWG FPE

Mechanical Properties

Rated temperature	80℃		
Bend radius	10 x D		
Operating temperature range:	-20℃ to 70℃		

Electrical Properties

at 20°C

Conductor resistance (at 20 ± 5 °C)	≤ 58 Ω/km		
Capacitance conductor to conductor	Nom. 12.50 pF/ft		
Capacitance Cond. to Other Conductor & Shield	Nom. 23 pF/ft		
Impedance	100 to 120 Ω		
Voltage	30V RMS (AWM2919)		

Fire Rating

LSZH: IEC 60332-1-1/2; IEC 60754-1 & 2; IEC 61034-2

PVC: IEC 60332-1-1/2;

Ordering Information

SAP 1C	UC P/N	Product Description	P.U
TBA	48222F	RS485 Serial Data 2P 22AWG, FPE, Tinned Cu Braid 85% PVC, Grey	500m/reel
TBA	48222FL	RS485 Serial Data 2P 22AWG, FPE, Tinned Cu Braid 85% LSZH, Black	500m/reel

Marking:

Marked in 1 meter intervals as follows:

Draka MMS RS485 <Part Number> <Pair Qty>P <XX>AWG <PVC/LSZH> <FC><BATCH CODE> <XXX>M

<XX>: denotes conductor size in AWG <FC> : Draka defined factory Code

<BATCHCODE>: Factory defined tracking code MM/YYYY or WW/YYYY

<XXX>: increasing length marking by 1metre





DRAKA RS485 2P 22AWG FPE

Logistic			
Packing:			
Wooden drum.			
Delivery Lengths:			
500m per drum.			

Enquiries

Please contact our local sales offices or mms.asia@prysmiangroup.com

Multimedia Solutions is the data communication portfolio of Prysmian Group and comprises all the necessary portfolio of cable solutions for data communication.

Ask about UCCONNECT™ for a complete Fibre Optics Solutions with 25 Years System Warranty.

Visit www.DrakaUC.com for more information.

© PRYSMIAN GROUP 2017, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.